



HEP-747-Z-A-C9(TA)

- Neat paper cutting
- High gear & Durable
- Compact & sophisticated structure
- Water and Oil proof, suitable the use in kitchen

MODEL	HEP-747-Z-A-C9(TA)
printing method	Direct Thermal
Effective print width	80mm
Dot density	8 dot/mm
Print dots per line	640 dot
Print head average resistance	650Ω±3%
Paper width	80 mm±2%
Dot pitch	0.125mm
Feed pitch	0.125*0.125mm
Max print speed	220 mm/s
Pulse life / mechanical life	1*10 ⁸ pulse/150Km
Print head temperature detection	Thermistor
Paper out detection	photoelectric sensor
Rubber roller fixing method	Detachable body for easy loading
Print head power supply working voltage	24 VDC±10%
Print head logic working voltage	3.13-5.25VDC
Paper entry and exit method	Paper Enter & Exit
Paper cutting method	Manual paper tearing
Operating temperature	5°C-45°C
Working humidity	20%-85%
Weight	395g
Dimensions	L=121mm,W=64.7mm,H=73.2mm



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

