

XP-365B

Thermal Barcode Printer

Xprinter®

- 127mm/s high print speed
- No ink or ribbon required , start printing by paper loading
- Can contain up to 82 mm diameter paper roll
- Over-heat prevented and durable print head
- Imported ROHM print head



Coffee Shop



Shopping




Mart



XP-365B

Thermal Barcode Printer



Model		XP-365B	
Print mode	Label print mode		Receipt print mode
Resolution	203 DPI		
Printing method	Direct Thermal		
Max.print speed	127 mm/s	90 mm/s	
Max.print width	76 mm		
Media			
Media type	Thermal roll paper, thermal adhesive paper		
Media width	20~80 mm		
Media thickness	0.06 ~ 0.19 mm		
Media roll diameter	Max.82 mm		
Supply method	Easy Paper Loading		
Performance Features			
Ram	4M		
Flash	4M		
Interfaces	USB / USB+Lan / USB+Serial+Lan / USB+Bluetooth/ USB+Wifi/ USB+Serial+Lan+Bluetooth / USB+Serial+Lan+Wifi		
Sensors	Print head temperature sensor/ Paper end/ Cover open / Gap		Print head temperature sensor/ Paper end/ Cover open
Drawer port	1 port (Pin 2 for cashdrawer)		
Fonts/Graphics/Symbologies			
Character sizes	Commonly used in single-byte fonts; FONT 0 to FONT 8, K, TST24.BF2,TSS24.BF2		
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A /UPCA+2 /UPCA+5/ UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14		
2D bar code	PDF417、QRCODE、DataMatrix		
Emulaion	TSPL	ESC/POS	
Physical Features			
Dimension	212×140×144mm (D×W×H)		
Weight	0.94 kg		
Reliability			
Print head life	100 km		
Software			
Driver	Windows		
SDK	iOS/ Android/ Windows		
Power supply			
Input	DC 24V/2.5A		
Environmental Conditions			
Operation	5~45 °C Humidity:RH 10 ~ 80%		
Storage environment	-40 ~ 55 °C Humidity:93% RH		



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

