

XP-P200

Mobile Receipt printer



Key features

- Easy paper loading structure design
- High speed printing
- Easy operate
- 7 days standby time
- Portable

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-P200

Mobile receipt printer



Printing		XP-P200
Printing method	Direct thermal	
Printing width	48mm	
Paper width	58mm	
Paper roll diameter	≤30mm	
Resolution	203 dpi	
Printing speed	80 mm/s	
Interface	USB+ Bluetooth (Optional : Serial)	
Line spacing	3.75mm (changeable using commands)	
Character size	ANK, Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese, traditional Chinese - 16 columns	
Barcode Character		
Extented character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII/ Latvian/ Arabic/ PT151(1251)	
Barcode types	1D: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D: QR CODE / PDF417	
Buffer		
Input buffer	32k bytes	
NV Flash	64k bytes	
Power		
Power supply	AC 110V/240V, 50 ~ 60Hz	
Power source	Output: DC 9V-2A	
Reliability		
Print head life	50 KM	
Physical characteristics		
Gross weight	0.22 kg	
Dimensions	111×88×41mm(D x W x H)	
Environmental Conditions		
Work environment	0 ~ 45℃, 10 ~ 80% RH	
Storage environment	-10 ~ 60℃, 10 ~ 90% RH (no condensation)	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

