

Xprinter®



Mobile Label Printer

XP-P4401B




- LCD screen, easy to operate
- Low noise, high quality, high speed printing
- 2500mAh large capacity battery, long standby
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS emulation compatible



XP-P4401B

Mobile Label Printer



Printing	XP-P4401B
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	Max. 100mm (3.937") / s
Max.print width	108 mm (4.25")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark
Media width	40 mm ~ 112 mm
Media thickness	0.06 mm ~0.254 mm
Paper roll diameter	50 mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	Stardard version: USB+Bluetooth Optional:USB+WIFI / NFC
Screen	1.3"OLED
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor
Performance Features	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°、90°、180°、270°
Emulaion	TSPL、EPL、ZPL、DPL、CPCL、ESC/POS
Physical Features	
Dimensions	150 mm (L) x 131 mm (W) x 64 mm (H)
Weight	583 g
Reliability	
Printer head life	30Km
Software	
Operation system	Windwos / Linux / Mac / Android / iOS
SDK	Windows / Android / iOS
Power supply	
Input/Output	Input: AC 100-240V,0.5A 50-60Hz ; Output: DC 5V/ 2A
Battery life	7.4V/2500mAh
Options	
Optional accessories	①Shoulder strap ②Protection bag ③Dual-slot battery charger
Environmental Conditions	
Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

