

Xprinter®

Thermal Transfer/ Direct Thermal


XP-TT424B/TT434B

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon internal diameter: 127mm (0.5")
- Bartender special edition



XP-TT424B / TT434B

Thermal Transfer/ Direct Thermal



Printing Features		XP-TT424B	XP-TT434B
Resolution	203 DPI		300 DPI
Print method	Thermal Transfer / Direct Thermal		
Max.Print speed	127 mm (5") / s	101.6 mm (4") / s	
Max.print width	108 mm (4.25")		
Max.print length	1778 mm (70")		
Media			
Media type	Continuous, gap, black mark, fan-fold and punched hole		
Media width	25.4-118mm (1.0"-4.6")		
Media thickness	0.06~0.254 mm (2.36~10mil)		
Media core diameter	25.4 ~ 50.8 mm (1" ~ 2")		
Ribbon length	Max.90m		
Ribbon width	25.4mm-110mm (1"-4.3")		
Label length	10 mm ~1778 mm	10 ~ 1016 mm (0.39" ~ 40")	
Label roll capacity	127 mm (5") OD (outside wound)		
Performance Features			
Processor	32-bit CPU		
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb		
Interface	Standard:USB Optional:WIFI/Bluetooth/TF card		
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor		
Fonts/Graphics/Symbologies			
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.		
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST		
2D barcode	PDF-417, Maxicode, DataMatrix, QR code		
Rotation	0°、90°、180°、270°		
Emulaion	TSPL、EPL、ZPL、DPL		
Physical Features			
Dimension	246mm*199mm*168mm (D*W*H)		
Weight	1.62kg		
Reliability			
Print head life	30 km		
Software			
Driver	Windows / Linux / Mac		
SDK	Windows / Linux / iOS		
Power supply			
Input	AC 100-240V		
Output	DC 24V, 2.5A		
Options			
Factory Options	①Bluetooth module ②WiFi module ③Real clock ④Cutter		
Dealer Options	① External paper roll holder ②Paper roll spindle ③Extension board for external paper roll holder ④Shipment waybill box		
Environmental Conditions			
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing		
Storage environment	-40 ~ 60°C(-40~140°F). Humidity:10 ~ 90% non-condensing		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

