

XP-58IIK

Direct thermal Printer



Key features

- Outstanding functions, Strong stability
- Support main stream systems
- Support OPOS driver
- Avoid order missing
- Support simplified/traditional Chinese, Japanese,
- Korean and many other international languages

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-58IIK

Direct thermal Printer



Printing		XP-58IIK
Printing method	Direct thermal	
Paper width	57.5±0.5mm	
Print width	48 mm	
Column capacity	384 dots/line	
Printing speed	90 mm/s	
Interface	USB / Lan / Serial / Parallel	
Line spacing	3.75mm (Adjustable by commands)	
Fonts Symbology		
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24	
Characters /Line	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets	
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
2D Barcode	QR code	
Input buffer	32 Kbytes / 64 Kbytes	
NV Flash	64 Kbytes	
Power		
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A	
Power source	DC 12V/2.6A	
Cash drawer	DC 12V/1A	
Physical characteristics		
Weight	0.73 kg	
Dimensions	180*132*112 mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 80%)	
Reliability		
Printer head life	50 KM	
Software		
Emulation	ESC/POS	
Driver	Windows/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS/ Android/ Windows	



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprinter.net](http://www.xprinter.net)
 Email: overseas@xprinter.net

