

XP-58IIK

Thermal Receipt Printer

Xprinter®

- High operational reliability
- Drop in paper loading
- Support QR code
- Supports a variety of international languages
- High print speed for both graphics and text



Coffee Shop



Shopping




Mart



XP-58IIK

Direct thermal Printer



Printing		XP-58IIK
Printing method		Direct thermal
Paper width		57.5±0.5mm
Print width		48 mm
Column capacity		384 dots/line
Printing speed		90mm/s
Interface		USB/USB+Serial / USB+Blueooth/ USB+Blueooth+Serial / USB+Blueooth+Serial+WiFi
Line spacing		3.75mm (Adjustable by commands)
Fonts Symbology		
Character size		Afont A: 12x24, Font B: 9x17, CHN: 24*24
Characters /Line		Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
1D Barcode		UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D Barcode		QR code
Input buffer		32 Kbytes
NV Flash		64 Kbytes
Power		
Power adaptor		Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A
Power source		DC 12V/2.6A
Cash drawer		DC 12V/1A
Physical characteristics		
Weight		0.498 Kg
Dimensions		121.8×110×114.6 mm (D×W×H)
Environmental Requirements		
Work environment		Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment		Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
Reliability		
Printer head life		50 KM
Software		
Emulation		ESC/POS
Driver		Windows/Linux/Android/Mac
Utility		Windows & Linux test Utility
SDK		iOS/ Android/ Windows



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

