

Direct thermal Printer

XP-C58K



Key features

- Big gear printing head
- Outstanding functions, Strong stability
- Support main stream OS systems
- Fast print speed : 120 mm/s
- Support Chinese GB18030
- Avoid order missing

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-C58K

Direct thermal Printer



Printing		XP-T58L	
Printing method	Direct thermal		
Paper width	57.5±0.5mm		
Print width	48 mm		
Column capacity	384 dots/line		
Printing speed	120 mm/s		
Interface	Parallel / Serial / USB / Lan / USB+Bluetooth / USB+Wifi		
Line spacing	3.75mm (Adjustable by commands)		
Fonts Symbology			
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24		
Characters /Line	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets		
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128		
Input buffer	32 Kbytes		
NV Flash	64 Kbytes		
Power			
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz		Output: DC 12V/2.6A
Power source	DC 12V/2.6A		
Cash drawer	DC 12V/1A		
Physical characteristics			
Weight	1.18 kg		
Dimensions	191×132×128mm (D×W×H)		
Environmental Requirements			
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)		
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 80%)		
Reliability			
Printer head life	50 KM		
Software			
Emulation	ESC/POS		
Driver	Windows/Linux/Android/Mac		
Utility	Windows & Linux test Utility		
SDK	iOS/ Android/ Windows		



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

