

Direct thermal Printer

XP-T58K



Key features

- The open button design, not only with fast printing speed, but also with better mold precision.
- With the perfect appearance structure design and complete function.
- It is the best choice for Chain Supermarket, Restaurant, Tax Institution warehouse etc to meet all kinds of printing needs.

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-T58K

Direct thermal Printer



Printing		XP-T58K
Printing method	Direct thermal	
Paper width	57.5±0.5mm	
Print width	48 mm	
Column capacity	384 dots/line	
Printing speed	120 mm/s	
Interface	Parallel / Serial / USB / Lan / USB+Bluetooth / USB+Wifi	
Line spacing	3.75mm (Adjustable by commands)	
Fonts Symbology		
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24	
Characters /Line	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets	
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
Input buffer	32 Kbytes	
NV Flash	64 Kbytes	
Power		
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A	
Power source	DC 12V/2.6A	
Cash drawer	DC 12V/1A	
Physical characteristics		
Weight	1.02 kg	
Dimensions	191×132×128mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 80%)	
Reliability		
Printer head life	50KM	
Software		
Emulation	ESC/POS	
Driver	Windows/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS/ Android/ Windows	



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

