

# XP-T58L

# Xprinter®

## Direct thermal Printer

- Big gear printing head
- Outstanding functions, Strong stability
- Support main stream OS systems
- Support simplified/traditional Chinese, Japanese, Korean and many other international Languages
- Support Chinese GB18030
- Avoid order missing
- Support OPOS driver



Restaurant



Shopping




Mart



Interface

# XP-T58L

## Direct thermal Printer



| Printing                   |  | XP-T58L                                                                               |
|----------------------------|--|---------------------------------------------------------------------------------------|
| Printing method            |  | Direct thermal                                                                        |
| Paper width                |  | 57.5±0.5mm                                                                            |
| Print width                |  | 48 mm                                                                                 |
| Column capacity            |  | 384 dots/line                                                                         |
| Printing speed             |  | 90mm/s                                                                                |
| Interface                  |  | USB / Parallel                                                                        |
| Line spacing               |  | 3.75mm (Adjustable by commands)                                                       |
| Fonts Symbology            |  |                                                                                       |
| Character size             |  | Afont A: 12x24, Font B: 9x17, CHN: 24*24                                              |
| Characters /Line           |  | Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets                              |
| 1D Barcode                 |  | UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 |
| Input buffer               |  | 32 Kbytes                                                                             |
| NV Flash                   |  | 64 Kbytes                                                                             |
| Power                      |  |                                                                                       |
| Power adaptor              |  | Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A                                    |
| Power source               |  | DC 12V/2.6A                                                                           |
| Cash drawer                |  | DC 12V/1A                                                                             |
| Physical characteristics   |  |                                                                                       |
| Weight                     |  | 0.68 kg                                                                               |
| Dimensions                 |  | 170 x 125 x 119.5mm (D×W×H)                                                           |
| Environmental Requirements |  |                                                                                       |
| Work environment           |  | Temperature (0 ~ 45°C) humidity(10 ~ 80%)                                             |
| Storage environment        |  | Temperature(-10 ~ 60°C) humidity(10 ~ 80%)                                            |
| Reliability                |  |                                                                                       |
| Printer head life          |  | 50 KM                                                                                 |
| Software                   |  |                                                                                       |
| Emulation                  |  | ESC/POS                                                                               |
| Driver                     |  | Windows/Linux/Android/Mac                                                             |
| Utility                    |  | Windows & Linux test Utility                                                          |
| SDK                        |  | iOS/ Android/ Windows                                                                 |



Scan QR code to checkout Xprinter website for more update information.  
 Phone: (+86 756) 3895 852  
[Http://www.xprintertech.com](http://www.xprintertech.com)  
 Email: [overseas@xprinter.net](mailto:overseas@xprinter.net)

